

TECHNICAL INFORMATION

TARMAC OVERBANDING TAPE

Product Data Sheet

DESCRIPTION

Tarmac Overbanding Tape is a high quality, durable thermoplastic preformed overbanding tape to seal joints in asphalt surfaces, preventing water ingress and preventing frost damage. **Tarmac Overbanding Tape** has been designed to retain its flexibility in colder conditions and is non-tacky in hot conditions. A pre-embedded anti-skid additive provides high PSV on application.

BENEFITS

- BBA HAPAS approved
- Waterproof
- Prevents frost damage
- Prolongs the life of an asphalt repair
- No waste – can be cut to size
- Easy to use
- Anti-skid – no additional drop on material required
- Seals cracks and joints
- Provides a durable, long lasting finish
- Can be trafficked in 10 minutes
- Achieves anti-skid SRV of 60.

SURFACE PREPARATION

All surfaces must be clean, dry and free from oil, grease, petrol and any other contamination that could adversely affect the bond. Loose and friable material should be removed or repaired.

EQUIPMENT

Portable universal medium gas torch and appropriate LPG cylinder.

A stiff bristled brush



APPLICATION

Sweep surface with stiff bristled brush ensuring surface is free from dust, dirt, etc.

Moisture should be removed from the surface by holding the gas torch 4-6 inches above the surface, steadily moving it from side to side until dry.

Cut **Tarmac Overbanding Tape** to the required length with a sharp knife. Place line in required position before heating.

Hold the gas torch 4-6 inches above the tape, and move from side to side to gradually heat up the material. **Tarmac Overbanding Tape** will melt and bond permanently to the surface. It is recommended to slightly over-heat the material to ensure it is correctly heated, but should not be severely overheated.

Once cool **Tarmac Overbanding Tape** can be trafficked immediately.

For more details contact:
03444 630 046 pozament@tarmacbp.co.uk

TARMAC.COM

The information supplied in our literature or given by our employees is based upon extensive knowledge and experience. This information, together with that supplied by our agents or distributors, is given in good faith in order to help you. Our Company policy is one of continuous Research and Development; we therefore reserve the right to update this information at any time without prior notice. We also guarantee the consistent high quality of our products; however, as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. Any existing intellectual property right must be observed. Tarmac's standard terms and conditions apply.

PACKAGING AND STORAGE

Tarmac Overbanding Tape is available in 5 metre rolls, 35mm wide.

Tarmac Overbanding Tape should be stored at a temperature of 5°C – 25°C.

QUALITY CONTROL

All Pozament products are factory blended, tested and packaged to quality control procedures in accordance with BS EN ISO 9001.

HEALTH & SAFETY

Health and safety advice, which must be followed, can be found on the Material Safety Data Sheet. Users are advised to wear face mask, goggles, gloves and overalls when handling, mixing and applying bituminous products.

INFORMATION, PRICES & ORDERING

For technical information, pricing and to place orders contact our Sales Office on the following:

Telephone: **03444 630 046**

Email: **pozament@tarmacbp.co.uk**

Visit our website: **Tarmac.co.uk**

Tarmac Building Products Ltd.,
Swains Park Industrial Estate, Park Road, Overseal,
Swadlincote, Derbyshire, DE12 6JT

For more details contact:
03444 630 046 pozament@tarmacbp.co.uk

TARMAC.COM

The information supplied in our literature or given by our employees is based upon extensive knowledge and experience. This information, together with that supplied by our agents or distributors, is given in good faith in order to help you. Our Company policy is one of continuous Research and Development; we therefore reserve the right to update this information at any time without prior notice. We also guarantee the consistent high quality of our products; however, as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. Any existing intellectual property right must be observed. Tarmac's standard terms and conditions apply.