

TECHNICAL INFORMATION

TARMAC THERMOPLASTIC LINE MARKING

Product Data Sheet

DESCRIPTION

Tarmac Thermoplastic Line Marking is a preformed thermoplastic used to lay permanent lines on asphalt surfacing. **Tarmac Thermoplastic Line Marking** is durable, easy to lay and meets the current Highways Standards.

BENEFITS

- Easy to use
- Cost effective
- No specialist equipment required
- Rapid curing time – minimal return to service time

COLOURS

Tarmac Thermoplastic Line Marking is available in White, Yellow, Primrose, Deep Cream & Red.

PREPARATION

The application surface should be sound and clean, free from oil, grease, rust, dirt or any other contaminant that could adversely affect the bond.



APPLICATION

Mark out the area in which the product is to be applied. Cut the marking to the correct size by scoring with a sharp knife and gently bending to snap clean. Use a gas torch to heat the surface where the product is to be laid. Remove any residual water or moisture using the torch. Place **Tarmac Thermoplastic Line Marking** and remove plastic film. Use the gas torch to heat, moving from side to side in a pendulum motion. Hold the torch no closer than 150mm and do not scorch the product.

To ensure maximum adhesion the material should be heated to 180-220°C. Apply heat until the whole area is fully bonded to the substrate.

Tarmac Thermoplastic Line Marking can be trafficked as soon as it is cool.

PACKAGING AND STORAGE

Tarmac Thermoplastic Line Marking is available in 5 metre roll lengths 100mm wide.

Tarmac Thermoplastic Line Marking has a minimum shelf life of 12 months. **Thermoplastic Line Marking** should be stored in original unopened boxes, under cover between 5-25°C and in dry conditions away from direct sunlight.

For more details contact:
03444 630 046 pozament@tarmacbp.co.uk

TARMAC.COM

The information supplied in our literature or given by our employees is based upon extensive knowledge and experience. This information, together with that supplied by our agents or distributors, is given in good faith in order to help you. Our Company policy is one of continuous Research and Development; we therefore reserve the right to update this information at any time without prior notice. We also guarantee the consistent high quality of our products; however, as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. Any existing intellectual property right must be observed. Tarmac's standard terms and conditions apply.

QUALITY CONTROL

All Pozament products are factory blended, tested and packaged to quality control procedures in accordance with BS EN ISO 9001.

HEALTH & SAFETY

Health and safety advice, which must be followed, can be found on the Material Safety Data Sheet.

INFORMATION, PRICES & ORDERING

For technical information, pricing and to place orders contact our Sales Office on the following:

Telephone: **03444 630 046**

Email: **pozament@tarmacbp.co.uk**

Visit our website: **tarmac.co.uk**

Tarmac Building Products Ltd.,
Swains Park Industrial Estate, Park Road, Overseal,
Swadlincote, Derbyshire, DE12 6JT

For more details contact:
03444 630 046 pozament@tarmacbp.co.uk

TARMAC.COM

The information supplied in our literature or given by our employees is based upon extensive knowledge and experience. This information, together with that supplied by our agents or distributors, is given in good faith in order to help you. Our Company policy is one of continuous Research and Development; we therefore reserve the right to update this information at any time without prior notice. We also guarantee the consistent high quality of our products; however, as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. Any existing intellectual property right must be observed. Tarmac's standard terms and conditions apply.